EcoFlow Solar Panel



110W Solar Panel

Rated Power 110W(±5W) 21-22% Efficiency

Cell Type Monocrystalline silicon

Output Ports MC4 Solar Port to XT60: 1000V(max), up to 12A (max)

Weight 13.2 lbs (6.0kg) Solar Panel 8.8 lbs (4.0kg) 20.2 × 16.5 × 0.8 in (51.4 × 42 × 2.0cm) Folded Dimension



160W Solar Panel

Rated Power 160W(±5W) 21-22% Efficiency Monocrystalline silicon Cell Type

MC4 Solar Port to XT60: 1000V(max), up to 12A (max) Output Ports

Weight 15.4 lbs (7.0kg) Solar Panel 11 lbs (5.0kg) Folded Dimension 26.8 × 16.5 × 1.0 in (68 × 42 × 2.4cm)



400W Solar Panel

Weight

Folded Dimension

Rated Power 400W(±5W) Efficiency 21-22% Cell Type Output Ports

Monocrystalline silicon

MC4 Solar Port to XT60: 1000V(max), up to 12A (max) 37.5 lbs (17.0kg) Solar Panel 27.6 lbs (12.5kg)

41.7 × 24.4 × 1.0 in (105.8 × 62 × 2.4cm)



EcoFlow was founded in 2017 with a mission is to empower people and communities through portable, clean, reliable power for lasting impact by dethroning the traditional gas generator and reinventing the way the world accesses energy.

We leverages our technology and experience to build products that are thoughtful in design, creating industry-first, smart and powerful energy storage products, and strive to reinvent the way people everywhere access power.

EcoFlow Technology Ltd.



■ ★ ■ Email: sales@ecoflow.com Tel: (001) 205 598 1962 Web: www.ecoflow.com

ECOFLOW

Power a New World



About EcoFlow Product

TECHONOLOGY

X-Stream (patented)

EcoFlow's patented X-Stream technology delivers one of the fastest recharging rates on the market. Using a built-in smart inverter, EcoFlow portable power stations can recharge from 0-80% in as quickly as 1 hour and to full within 2 hours.

X-Boost

EcoFlow's X-Boost technology lets you power devices that have higher rated power than your portable power station. This unique technology delivers power for your essential devices in any situation. We recommend conducting a test with your devices with X-Boost turned on.

Smart BMS

(Battery Management System)

Smart and powerful management for efficient and safety using experience.

EcoFlow APP

Intelligent control for every EcoFlow product in the palm of your hand.

APPLICATION

OUTDOOR

- Road Trips
- Camping





EMERGENCY

- Home Backup
- Disaster Relief
- Medical Services



PROFESSIONAL

- DIY/Construction
- Photography
- Event Production



EcoFlow RIVER Series

RIVER mini (wireless) X- TREAM X-800 T

AC Output 300W (Surge 600W)

Capacity 210Wh

Output Ports 8 (AC × 2. including wireless charging)

Weight 6.3lbs (2.85ka) 9.8" x 5.5" x 5.2" Dimension

1.5h (300W Wall Charge) Recharge Time

> 2-4h (160W Solar Panel) 2.5-3.5h (96W Car Charge)

Runtime reference









Car Fridge

RIVER

X- TR=AM X-800 T

AC Output 600W (Surge 1200W) 288Wh Capacity

10 (AC × 3) Output Ports 11lbs (5.0kg) Weight 11.3" x 7.3" x 7.7" Dimension

Recharge Time 1.6h (250W Wall Charge) 1.6-3h (2 × 110W Solar Panel)

2.5h (96W Car Charge)







Runtime reference















RIVER Max X-TREAM X-800 T

AC Output 600W (Surge 1200W)

Capacity 576Wh Output Ports 10 (AC × 3) Weight 17lbs (7.7kg) 11.4" x 7.3" x 9.3" Dimension Recharge Time 1.6h (500W Wall Charge)

3-6h (2 × 110W Solar Panel) 5h (96W Car Charge)

Runtime reference











RIVER Pro X-7TREAM X-800/T

AC Output 600W(Surge 1200W)

Capacity 720Wh Output Ports 10 (AC × 3) 16.8lbs (7.6kg) Weight Dimension 11.4" x 7.1" x 9.3" Recharge Time

1.6h (660W Wall Charge) 4-8h (2 × 110W Solar Panel) 6.5h (96W Car Charge)



Runtime reference











Hair Drver

EcoFlow DELTA Series

DELTA mini X-7TREAM X-BOOTT

AC Output 1400W (Surge 2100W)

Capacity 882Wh Output Ports 12 (AC × 5) Weight 23.6 lbs (10.7a) Dimension 14.9" x 7.2" x 9.4"

Recharge Time 1.6h (900W Wall Charge)

3.7-7.4h (2 × 160W Solar Panel)

9.5h (96W Car Charge)

Runtime reference











X-TREAM **DELTA**

AC Output 1800W(Surge 3300W)

1260Wh Capacity 13 (AC × 6) Output Ports Weiaht 30.9 lbs (14.0 kg) 15.7" x 8.3" x 10.6" Dimension Recharge Time 1.6h (1200W Wall Charge)

> 4-8h (4 × 110W Solar Panel) 14h (96W Car Charge)



Runtime reference













DELTA Max X-TREAM X-800 T

AC Output 2400W(Surge 5000W)

2016Wh Capacity Output Ports 15 (AC × 6) 22 lbs (48 kg) Weight 19.6" x 9.5" x 12" Dimension

Recharge Time 1.8h (1800W Wall Charge) 3.2-6.3h (2 × 400W Solar Panel)

21h (96W Car Charge)



Runtime reference











DELTA Pro X-FTREAM X-800/T

AC Output 3600W(Surge 7200W) Capacity 3600Wh

Output Ports 15 (AC × 5) Weight 99 lbs (45 kg) Dimension 25" x 11.2" x 16.6"

Recharge Time 2.7h (1800W Wall Charge) $4-8h (3 \times 400W Solar Panel)$

37.5h (96W Car Charge)









Runtime reference



